

Temp.	Temp.	Widerstandswert		
		Resistance Value		
		Max.	Standard	Min.
Deg. F	°C	KW	KW	KW
-58.00	-50	344.4	329.2	314.7
-56.20	-49	324.7	310.7	297.2
-54.40	-48	306.4	293.3	280.7
-52.60	-47	289.2	277	265.3
-50.80	-46	273.2	261.8	250.6
-49.00	-45	258.1	247.5	237.2
-47.20	-44	244	234.1	224.6
-45.40	-43	230.8	221.6	212.7
-43.60	-42	218.5	209.8	201.5
-41.80	-41	206.8	198.7	191
-40.00	-40	195.9	188.4	181.1
-38.20	-39	185.4	178.3	171.59
-36.40	-38	175.5	168.9	162.5
-34.60	-37	166.2	160.1	154.1
-32.80	-36	157.5	151.8	146.1
-31.00	-35	149.3	144	138.8
-29.20	-34	141.6	136.6	131.8
-27.40	-33	134.4	129.7	125.2
-25.60	-32	127.6	123.2	118.9
-23.80	-31	121.2	117.1	113.1
-22.00	-30	115.1	111.3	107.5
-20.20	-29	109.3	105.7	102.2
-18.40	-28	103.8	100.4	97.16
-16.60	-27	98.63	95.47	92.41
-14.80	-26	93.75	90.8	87.93
-13.00	-25	89.15	86.39	83.7
-11.20	-24	84.82	82.22	79.71
-9.40	-23	80.72	78.29	75.93
-7.60	-22	76.85	74.58	72.36
-5.80	-21	73.2	71.07	68.99
-4.00	-20	69.74	67.74	65.8
-2.20	-19	66.42	64.54	62.72
-0.40	-18	63.27	61.52	59.81
1.40	-17	60.3	58.66	57.05
3.20	-16	57.49	55.93	54.39
5.00	-15	54.83	53.39	51.97
6.80	-14	52.31	50.96	49.83
8.60	-13	49.93	48.65	47.12
10.40	-12	47.67	46.48	45.31
12.20	-11	45.53	44.41	43.32
14.00	-10	43.5	42.25	41.43
15.80	-9	41.54	40.56	39.59
17.60	-8	39.68	38.76	37.85
19.40	-7	37.91	37.05	36.2
21.20	-6	36.24	35.43	34.02
23.00	-5	34.65	33.89	33.14
24.80	-4	33.14	32.43	31.73
26.60	-3	31.71	31.04	30.39
28.40	-2	30.35	29.72	29.09
30.20	-1	30	28.47	27.89
32.00	0	27.83	27.28	26.74

Temp.	Temp.	Widerstandswert		
		Resistance		
		Max.	Standard	Min.
Deg. F	°C	KW	KW	KW
33.80	1	26.64	26.13	25.52
35.60	2	25.51	25.03	24.55
37.40	3	24.24	23.99	23.54
39.20	4	23.42	22.99	22.57
41.00	5	22.45	22.05	21.66
42.80	6	21.52	21.15	20.78
44.60	7	20.64	20.29	19.95
46.40	8	19.8	19.4	19.15
48.20	9	19	18.7	18.4
50.00	10	18.24	17.96	17.67
51.80	11	17.51	17.24	16.97
53.60	12	16.8	16.55	16.31
55.40	13	16.13	15.9	15.87
57.20	14	15.5	15.28	15.06
59.00	15	14.89	14.68	14.48
60.80	16	14.31	14.12	13.93
62.60	17	13.75	13.57	13.4
64.40	18	13.22	13.06	12.89
66.20	19	12.72	12.56	12.41
68.00	20	12.23	12.09	11.95
69.80	21	11.77	11.63	11.57
71.60	22	11.32	11.2	11.07
73.40	23	10.9	10.78	10.6
75.20	24	10.49	10.38	10.27
77.00	25	10.1	10	9.9
78.80	26	9.73	9.63	9.52
80.60	27	9.38	9.28	9.18
82.40	28	9.04	8.94	8.84
84.20	29	8.72	8.62	8.52
86.00	30	8.41	8.31	8.21
87.80	31	8.11	8.01	7.91
89.60	32	7.82	7.72	7.62
91.40	33	7.55	7.45	7.35
93.20	34	7.28	7.19	7.09
95.00	35	7.03	6.94	6.84
96.80	36	6.79	6.69	6.6
98.60	37	6.56	6.46	6.37
100.40	38	6.33	6.24	6.15
102.20	39	6.12	6.03	5.94
104.00	40	5.92	5.82	5.73
105.80	41	5.72	5.63	5.54
107.60	42	5.53	5.43	5.35
109.40	43	5.34	5.25	5.17
111.20	44	5.16	5.08	4.99
113.00	45	4.99	4.91	4.82
114.80	46	4.83	4.74	4.66
116.60	47	4.67	4.59	4.51
118.40	48	4.52	4.44	4.36
120.20	49	4.38	4.3	4.22
122.00	50	4.24	4.16	4.08
123.80	51	4.1	4.02	3.95
125.60	52	3.97	3.9	3.82
127.40	53	3.84	3.77	3.69
129.20	54	3.72	3.65	3.57
131.00	55	3.61	3.53	3.46

Temp.	Temp.	Widerstandsw		
		Resistance		
		Max.	Standard	Min.
Deg. F	°C	KW	KW	KW
132.80	56	3.49	3.42	3.35
134.60	57	3.39	3.31	3.24
136.40	58	3.28	3.21	3.14
138.20	59	3.18	3.11	3.04
140.00	60	3.09	3.02	2.95
141.80	61	2.99	2.92	2.86
143.60	62	2.9	2.83	2.77
145.40	63	2.81	2.75	2.69
147.20	64	2.73	2.66	2.6
149.00	65	2.65	2.58	2.52
150.80	66	2.57	2.51	2.45
152.60	67	2.49	2.43	2.37
154.40	68	2.42	2.36	2.3
156.20	69	2.35	2.29	2.24
158.00	70	2.28	2.22	2.17
159.80	71	2.21	2.16	2.1
161.60	72	2.15	2.1	2.04
163.40	73	2.09	2.04	1.98
165.20	74	2.03	1.98	1.93
167.00	75	1.97	1.92	1.87
168.80	76	1.92	1.87	1.82
170.60	77	1.86	1.81	1.78
172.40	78	1.81	1.76	1.71
174.20	79	1.76	1.71	1.68
176.00	80	1.71	1.66	1.62
177.80	81	1.66	1.62	1.57
179.60	82	1.62	1.57	1.53
181.40	83	1.57	1.53	1.49
183.20	84	1.53	1.49	1.44
185.00	85	1.49	1.45	1.4
186.80	86	1.45	1.41	1.37
188.60	87	1.41	1.37	1.33
190.40	88	1.37	1.33	1.29
192.20	89	1.34	1.3	1.26
194.00	90	1.3	1.26	1.22
195.80	91	1.27	1.23	1.19
197.60	92	1.23	1.2	1.16
199.40	93	1.2	1.16	1.13
201.20	94	1.17	1.13	1.1
203.00	95	1.14	1.1	1.07
204.80	96	1.11	1.08	1.04
206.60	97	1.08	1.05	1.01
208.40	98	1.05	1.02	0.99
210.20	99	1.03	0.99	0.96
212.00	100	1	0.97	0.94
213.80	101	0.98	0.94	0.91
215.60	102	0.95	0.92	0.89
217.40	103	0.93	0.9	0.87
219.20	104	0.91	0.87	0.84
221.00	105	0.88	0.85	0.82
222.80	106	0.86	0.83	0.8
224.60	107	0.84	0.81	0.78
226.40	108	0.82	0.79	0.76
228.20	109	0.8	0.77	0.74
230.00	110	0.78	0.75	0.73